

RGB30X-POE-WH

30X PTZ Camera



Key Features

- High speed optical zoom
- High performance in low light scenarios with Wide Dynamic Range
- Full 1920×1080p HD Resolutions up to 60 frames per second
- H.265/H.264 Dual Stream Output Adapted to Different Network Environments
- Pan and Tilt Control
- Wide Application
- Low-power Sleep Function
- Support PoE(IEEE 802.3af 48V)

Specification

Connectors	Video(Output)	HDMI	1×HDMI-A
		SDI	1×BNC
		LAN(Support PoE)	1×RJ45
	Audio	Input	1×3.5mm Stereo Jack
	Communication	RS232	2×DIN 8
		RS485	1×2 Pin Connector
		Network	1×100Mbps (10/100BASE-TX)
	Power		1×HEC3800 DC Socket
Performance	Camera	Optical Zoom	30X f=4.9~129mm
		View Angle	2.34°~65.1°
		AV	F1.6 ~ F4.7
		Minimum Illumination	0.5Lux (F1.8 ,AGC ON)
		DNR	2D & 3D DNR
		White Balance	Auto/Manual/One Push/3000K/3500K/4000K/4500K/5000K/5500K/6000K/6500K/7000K
		Focus	Auto/Manual
		Aperture/Electronic Shutter	Auto/Manual
		BLC	ON/OFF
		WDR	OFF/Dynamic Level Adjustment
		Video Adjustment	Brightness/Color/Saturation/Contrast/Sharpness/B/W mode/Gamma curve
		SNR	>55dB
		Effective Pixels	2.07m,16:9
	Pan-and-Tilt Parameter	Pan/Tilt Movement	-170°~+170°/-30°~+90°
		Pan/Tilt Control Speed	0.1~60°/S ; 0.1~30°/S
		Preset Speed/Quantity	Pan:60°/S, Tilt:30°/S; Up to 255 preset positions (10 remote control)
	Audio Compression Format	AAC,MP3,G.711A	
	Video Compression Format	H.264, H.265,Dual Streaming Output	
	Output Resolutions	720p25/29.97/30/50/59.94/60 1080p25/30/29.97/30/50/59.94/60	
	Control Protocol	VISCA Pelco-D Pelco-P	
	Baud Rate(bps)	115200 9600 4800 2400bps	
	Network Protocol	RTSP RTMP ONVIF GB/T28181 VISCA	
	Supported Standards	HDMI	1.3
		SDI	SMPTE 425M (Level A & B) SMPTE 424M SMPTE 292M SMPTE 259M-C DVB-ASI
Power	Input Voltage	DC12V/1.5A	
	Max Power	12W	
Environment	Temperature	-10℃~50℃	
	Humidity	20%~80%	
Physical	Weight	Net	1.4kg
	Dimension	Net	150mm×150mm×167.5mm

Order Codes

Product Code	Item
981-0011-15-0	RGB30X-POE-WH 30X PTZ Camera(Support PoE)

Dimension

