

VA210 - Video Conferencing System Kit

VA210 is a perfect conference solution that combines audio and video. It applies advanced ISP processing algorithms to provide vivid images with a strong sense of depth, high resolution, and fantastic color rendition. The audio adopts the international advanced new-generation high-definition voice processing technology with clear and smooth sound quality and strong environmental adaptability. It can provide participants with smooth and natural audiovisual effects whenever and wherever, and provide a comfortable and immersive experience for teleconferencing and other applications.









Key Features



1/2.9 inch high quality CMOS sensor. Resolution is up to 1920x1080. Low Noise CMOS effectively ensure high SNR of camera video.



3x zoom lens and 10x zoom lens are available, with 85° wide view angle without distortion.



Leading auto focus algorithm makes lens a



- fast, accurate and stable auto-focusing.
- Adopting high accuracy step motor and motor driving controller to make extremely quiet and smooth rotation .





microphone is available, up to 10m sound-pickup diameter. USB plug-and-play, supports various online conference software platforms such as

WeChat, Skype for Business, Zoom, Vidyo, etc.

6m sound-pickup diameter, external

Support AEC(Acoustic Echo Cancellation,

noise compression), Automatic Direction

finding Technology of Intelligent

in vocal full frequency domain

AGC(Automatic Gain Control),NC(Bidirectional

microphone(EMI), Zero damage compression

Built-in 4 single-point microphones, composed

of 360-degree omni-directional audio-pickup,



Built-in Up/Down, Left/Right, Answer, Hang up, Bluetooth, Presets, and other keys. Centralized connecting with the centralized controller VA200-H, the wiring is simpler and nicer.

TECHNICAL SPECIFICATION

Spec/Model NO.	VA210-V Fu	III HD PTZ Camera
Sensor	1/2.9 inch high quality HD CMOS sensor	
Effective Pixels	2.07M,16: 9	
Optical zoom lens	3X Optical zoom f=3.35~10.05mm	10X Optical Zoom f=4.34~41.66mm
View angle	30° (tele) 85° (wide)	8.8° (Tele) 68.8° (Wide)
Aperture value	F1.7 – F3.0	F1.85 – F2.43
Digital Zoom	10X	
Minimum Illumination	2D & 3D DNR	
DNR	0.5Lux(F1.8, AGC ON)	
White Balance	Auto / Manual/ One Push/3000K/3500K/4000K/4500K/5000K/5500K/6000K/6500K/7000K	
Video Format	1920×1080P@30 fps/25fps; 1280×720P@30fps/25fps; 1024×576P@30fps/25fps; 960×540P@30fps/25fps; 800×448P@30fps/25fps; 640×360P@30fps/25fps;320×176P@30fps/25fps	
Focus	Auto/Manual/One Push	
Aperture/Electronic Shutter	Auto/Manual	
BLC	ON/OFF	
WDR	OFF/ Dynamic level adjustment	
Video Adjustment	Brightness, Color, Saturation, Contrast, Sharpness, B/W mode, Gamma curve	
SNR	>55dB	
Rotation angle	Pan: -170°∼+170°, Tilt:-30°∼+90°	
Control speed	Pan: 0.1 ~60°/sec, Tilt:0.1~30°/sec	
Preset speed	Pan: 60°/sec, Tilt: 30°/sec	
Dimension	156.8mm×112.6mm×139.5mm (L×W×H)	

Spec/Model NO.	VA210-A Wireless Speakerphone
Voice technical parameters	Acoustic Echo cancellation (AEC): >65dB Echo length cancellation: ≥400ms Bidirectional noise compression (NC): <25dB Automatic Direction finding Technology of Intelligent microphone (EMI) Automatic gain control (AGC)
Audio parameters	Microphone frequency response: 100Hz-22KHz Speaker frequency response: 100Hz-22KHz Speaker volume: 95dB at the most Microphone sound-pickup diameter: 6 meters, 360 degrees full range
Bluetooth	Bluetooth devices available
IR Reception	Angle: 360° Distance: 10m IR Transparent transmission available 2 external microphones cam be connected,
External Mic (optional)	making the sound-pickup diameter up to 10 meters
Dimensions	200mm×200mm×55.9mm(L×W×H)

Spec/Model NO.	Centralized Controller VA210-H
Interface	Mini DIN6 ×2 Power interface×1 Power switch×1 Mini USB interface×1
Power supply	EC3800 plug(DC12V) Adapter input AC110V-AC220V output DC12V/1.5A
Data line	Mini DIN6 data line ×2 Length: 5m(10m/15m for options)
USB cable	USB2.0 cable (3m)
Compatibility	Support Windows, Andriod, iOS and Linux Drive-free automatic recognition of cameras microphones and speakers Compatible with Zoom, Lynch, Vidyo, etc.
Dimension	120mm×74mm×34.5mm(L×W×H)
Accessories	Power adapter, USB2.0 cable, Remote controlle two DIN6 connection cables, user manual

DIMENSION(MM):



156.8mm



112.6mm







SHENZHEN MINRRAY INDUSTRY CO.,LTD