

Pocket Speakerphone Hub

Small hub. Big connectivity with your impressive visualization and immersive sound

Technical Specifications

I/O Ports:

- 1 x HDMI 1.4 port (4K@30Hz)
- 1 x USB 3.2 Gen 2 Type-A port (Super Speed 10Gbps)
- 1 x USB 3.2 Gen 2 Type-C port (Power Delivery up to 100w)

Speaker

- 3 W
- Frequency Response: 150Hz 14kHz

Microphone

- 360 degrees, omni-directional
- Frequency Response: 150Hz 7kHz
- Pickup Range: 3 m/9.8 ft.

DSP (Digital Signal Processing)

- Al Noise Reduction
- Acoustic Echo Cancellation

Connection

- Plug and play (no driver needed)
- USB Type-C, manageable pigtail cable 43 cm/17.05 in.

Interface

 Al Noise Reduction, Microphone mute, Volume up, Volume down with LED indicators

Dimensions

Diameter x Height: 96 mm x 29.5 mm (3.8 x 1.2 in.)

*Specifications are subject to change without prior notice.

- Weight: 145.4 g (5.1 oz.)

System Requirements

- Windows (include surface), macOS (MacBook and iMac), Chromebook
- Available USB Type-C port (*with DP Alt mode for HDMI output)

Compatible to 3rd Party software

 Teams, Zoom, Google Meet, Cisco Webex, Skype, GotoWebinar, Wechat, Messenger, YouTube, Line, FaceTime

What's in the Box

- AS315 Speakerphone Hub
- Carry bag
- Quick Guide

Package Dimensions

- Unit: 131 x 114 x 65 mm (5.16 x 4.49 x 2.56 in.)
- Carton: 35.1 x 27.4 x 25.5 cm (13.82 x 10.79 x 10.04 in.)

Shipping Weights -20 in 1

- Unit: 122 g (4.30 oz.)
- Carton: 5.532 Kg (12.20 lb.) (20 pcs per carton)

Made in Taiwan



EAN	(71120050072
EAN	4711289500032
UPC	850036764076

AS315

©2022 by AVerMedia Technologies, Inc. All right reserved. AVerMedia is a registered trademark of AVerMedia Technologies, Inc. All other trademarks belong to their respective companies.

*Please visit the AVerMedia official website at www.avermedia.com for the latest information.

