



Nine-pin dot matrix printer offering faster printing, outstanding reliability and extremely low TCO.

The FX-890II is a high-volume, low TCO 80-column dot matrix printer designed for fast, reliable printing. A contemporary new design and small footprint make upgrading easy and add a range of new features for unprecedented flexibility.

### Market-leading print speeds<sup>1</sup>

The FX-890II offers an improved USD (ultra speed draft) speed of 735 characters per second at 12 characters per inch, making a real difference to high-volume print runs such as stock reports and large batches of invoices or freight documents.

### Outstanding reliability

Epson's dot matrix technology is already mature and very reliable, and these new printers improve the mean time between failure by 25% to 25,000 power-on hours, ideal for challenging conditions or where regular maintenance is not practical.

### Modern design

Epson's new range of dot matrix printers have a refreshingly modern design to fit in with your working environment.

## KEY FEATURES

- **Market-leading print speeds**  
Complete high-volume print runs even faster
- **Very low TCO**  
Cheap, long-lasting consumables and low power use
- **Even better reliability**  
Improved by 25% to 25,000 power-on hours
- **Modern design**  
Fits with your working environment
- **Energy Star compliant**  
To ensure the best possible energy efficiency

## PRODUCT SPECIFICATIONS

### TECHNOLOGY

Printing Method	Impact dot matrix
Number of Pins	9 pins
Number of columns	80 columns
Pins	18 Needles (2 x 9)

### PRINT

Printing Speed	HighSpeed-Draft: 10 cpi: 612 chars/s, Draft: 10 cpi: 463 chars/s, NLQ: 10 cpi: 115 chars/s
Barcodes	Coda bar (NW-7), Code 128, Code 39, Industrial 2 of 5, Matrix 2 of 5, POSTNET, UPC-A, UPC-E
Carbon Copies	6 plus one original
Character Sets	42
Character Tables	PCAPTEC, PC437, PC720, PC850, PC858, ISO-8859-15, Roman 8, Italic
Printing Resolution	240 x 144 DPI

### CONNECTIVITY

Interfaces	USB - compatible with USB 2.0 specification, Bidirectional parallel
------------	---

### PAPER / MEDIA HANDLING

Document Feed	Single sheet front and rear, Continuous media front and rear, Paper output rear
Paper Formats	Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Envelopes, Cardboard
Paper Thickness Continuous Paper	0,46 mm
Paper Thickness Label Base Sheet	0,46 mm
Paper Thickness Multi Part	0,12 mm - 0,46 mm
Paper Thickness Single Sheet	0,06 mm - 0,14 mm

### GENERAL

Power consumption	54 Watt, 0,5 Watt (economy), 8 Watt (standby)
Supply Voltage	AC 198 V - 264 V
Product dimensions	414 x 375 x 177 mm (Width x Depth x Height)
Product weight	7,2 kg
Supported Temperature	Operation 5° C - 35° C, Storage -30° C - 60° C
Supported Humidity	Operation 10% - 80%, Storage 30% - 60%
Mean Time Between Failures	25.000 hours
Print Head Life	400 Million Strokes/Wire
Fonts	Bitmap font EPSON Draft (10 CPI, 12 CPI, 15 CPI), Bitmap font EPSON OCR-B (10 CPI), Bitmap font EPSON Roman (10 CPI, 12 CPI, 15 CPI, Proportional), Bitmap font EPSON Sans Serif (10 CPI, 12 CPI, 15 CPI, Proportional)
Noise Level	Operation (Roll): 55 dB (A)
Ribbon Yield	7500000 characters Black Draft

### OTHER FEATURES

Emulations	ESC/P, IBM PPDS
Input Data Buffer	128 kB

### OTHER

Warranty	12 months Carry in
----------	--------------------

## FX-890II

## WHAT'S IN THE BOX

- Driver and utilities (CD)
- User guide
- AC cable
- Ribbon

## SUPPLIES

- Epson SIDM Black Ribbon Cartridge for FX-890, FX-890A (C13S015329) C13S015329

## FX-890II

## OPTIONAL ACCESSORIES

- Pull Tractor Unit  
C12C933761
- Epson SIDM Paper Roll Holder for LX-300+II/1170II, FX-890/A, FX-2190, LQ-690/300+II series  
C12C811141
- Epson SIDM Single Sheet Feeder 150 sheets for LQ-590, FX-890/A  
C12C806382
- Epson SIDM Single Sheet Feeder 50 sheets for FX-890/A, LX/LQ-300+II, LQ-590  
C12C806372

## LOGISTICS INFORMATION

SKU	C11CF37401
EAN code	8715946634487
Country of Origin	Indonesia
Layer	2 Units

1. Speeds compared with published specifications for directly competing products, May 2017.

**EPSON®**