

# PowerLite® L690E

6,500-Lumen 3LCD Laser Projector with 4K Enhancement



Experience an incredibly bright and compact projector with pro-level features.







**Bright, true-to-life images** — 3-chip 3LCD technology and 6,500 lumens of equal color and white brightness<sup>2</sup>

**WUXGA with 4K Enhancement Technology**<sup>1</sup> — accepts 4K content and displays double HD resolution on-screen; enjoy a visibly sharper, more detailed picture even at close viewing distances

**Large, versatile display options** — easily create a display up to 500" diagonal in 16:10, plus ultra wide 16:6 and 21:9 aspect ratios for enhanced content display and visibility

**Simplified installation** — compact and lightweight design featuring a wide vertical and horizontal lens shift, 1.6x optical zoom, 360-degree mounting, built-in geometric correction tools and a universal VESA mounting pattern

**Low maintenance** — up to 30,000-hour laser light source and air filter<sup>3</sup> in Extended Mode

**Wireless networking and content sharing**<sup>4</sup> — Wi-Fi<sup>®</sup> 6/6E allows for fast, reliable wireless connectivity for screen casting<sup>4</sup>, along with direct connection to the cloud-based service, Epson Projector Management Connected and WPA3-Enterprise security

**Built-in NFC**<sup>5</sup> — reduces installation time of multiple projectors; read and write setting information using the Epson Projector Config Tool app

**Optional attachable PixAlign™ camera** — adds powerful multiprojector tools including screen matching<sup>6</sup>, auto color calibration<sup>6</sup>, blending assist<sup>7</sup> for super wide displays and simple stacking<sup>7</sup> without an external PC

**Over-the-air updates**<sup>8</sup> — allows user to optionally be alerted when a Firmware update is available

**Enhanced connectivity** — HDBaseT® and HDMI® two in and one out for daisy-chaining and signal monitoring



# PowerLite® L690E 6,500-Lumen 3LCD Laser Projector with 4K Enhancement<sup>1</sup>

#### **Specifications**

Projection System RGB liquid crystal shutter projection system Projection Method Front/rear/ceiling mount

LCD Size 0.67" (C2Fine)

**Driving Method** Poly-Silicon TFT Active Matrix Pixel Number 2,304,000 dots (1920 x 1200) x 3 Native Resolution WUXGA with 4K Enhancement<sup>1</sup> (1920 x 1200 x 2)

Resolution On-Screen WUXGA with 4K Enhancement<sup>1</sup>/ 4.6 million pixels

**Resize** 640 x 480, 800 x 600, 1280 x 1024, 1400 x 1050

Aspect Ratio 16:10

Pixel Arrangement Cross stripe

Color Brightness<sup>2</sup> Color light output: 6,500 lumens White Brightness<sup>2</sup> White light output: 6,500 lumens

Contrast Ratio Over 5,000,000:1 **Brightness Uniformity (Typical)** 88%

Color Reproduction Up to 1.07 billion colors

Size (Projected Distance) 50" - 500'

Projected Distance 80" screen 2.33 m - 3.78 m Lens Shift (Manual) Vertical: ±50%; Horizontal: ±20%

Keystone Correction Vertical: ±30 degrees;

Horizontal: ±30 degrees **Light Source** Laser Diode

Laser Light Source Life<sup>3</sup> Normal: 20,000 hours: Quiet: 20,000 hours; Extended: 30,000 hours

## **Projection Lens (Standard)**

Type Optical Zoom (manual)/Focus (manual)

**F-Number** 1.5 - 1.7

Focal Length 20.0 mm - 31.8 mm

Zoom Ratio 1.0 - 1.6x (optical) Throw Rate Range 1.35 – 2.20 (optical) Lens Cover Lens cap (without string)

## **Wireless Specifications**

Frequency Type (Modulations) 802.11b/g/n/ac/ax (2.4 GHz) Supported Security Type Quick Mode: Open, WPA2/ WPA3-PSK, WPA2/WPA3-EAP; Advanced Mode: WPA/ WPA2-PSK, WPA/WPA2-EAP

### **Other Features**

Operating Temperature 32 °F to 113 °F (0 °C to 45 °C) Power Supply Voltage  $100~V-240~V\pm10\%,\,50/60~Hz~AC$ Auto Power On Signal Detection on HDMI/Plug-In Detection

Sleep Mode Yes (with timer) **HDMI CEC Control** Yes

**Power Consumption** 

415 W (Normal Mode)

305 W (Quiet and extended) 2.4 W (Standby comm on)

0.3 W (Standby comm off)

Fan Noise 32 dB (Normal Mode); max. 25 dB (ECO Mode)

Security Security cable hole, Kensington® lock provision

A/V Mute Yes

Miracast®4 Yes

Epson iProjection™ Yes (V4)

#### Interfaces

HDMI (HDCP 2.3) x 2 HDMI Out x 1 HDBaseT x 1 Variable Audio Out: Mini Stereo x 1 USB Connector Type-A x 1 USB Connector Type-B x 1 Serial: RS-232c x 1 Wired LAN RJ45 x 1 Wireless I AN: Built-in



## **Other Features (Continued)**

Split Screen<sup>9</sup> Yes (up to 2 screens)

Camera Yes

Speaker(s) 10 W (mono) Content Playback Yes **Quick Corner** Yes

**Corner Wall** Yes

**Curved Surface Yes Edge Blending Yes** 

Screen Sharing Yes

# **Effective Scanning Frequency Range (Digital)**

Pixel Clock 25.1 MHz - 594 MHz Horizontal 26 kHz - 135 kHz

Vertical 23.98/24/25/29.97/30/50/59.94/60 Hz

#### Dimensions (W x D x H)

Excluding Feet 17.32" x 11.97" x 4.80" Including Feet 17.32" x 13.39" x 5.43"

Weight 18.1 lb

## **Network and Remote Control**

Features Power, source search selection, AV Mute, number input, menu, esc, select, Freeze, ID, Customize, E-Zoom, mute, volume, playback control and pointer functions

Operating Angle Rear: Right/Left: -55 to +55 degrees; Upper/Lower: +75 to +15 degrees; Front: Right/Left: -30 to +30 degrees; Upper/Lower: 0 to +60 degrees

Operating Distance 26 ft (8 m)

Network Control PJLink, Creston Integrated partner, Crestron Connected V2 with XiO Cloud, Extron IP link, Extron XTP, AMX, Control4

# **Eco Features**

RoHS compliant

End-of-life options available<sup>10</sup>

Epson America, Inc. is a SmartWay® Transport Partner11

Design and Manufacturing centers utilize 100% renewable electricity Dynamic Contrast (ECO) Mode reduces power consumption by 36%

# **Limited Warranty and Service**

Warranty Three-year limited in the U.S. and Canada Service Whole unit exchange, usually Next-Business-Day Toll-free telephone support, Monday through Friday

**Epson Connection™** 

Pre-Sales Support (U.S. and Canada): 800-463-7766

Website: www.epson.com

#### Epson Preferred Plus™ Extended Service Plan<sup>12</sup>

1-Year Next-Business-Day Whole Unit Exchange13 EPPEXPE1 2-Year Next-Business-Day Whole Unit Exchange<sup>13</sup> FPPFXPF2 (available for up to a total of 5 years of continuous coverage)

#### What's Included

PowerLite L690E laser projector, power cable, projector remote control with batteries, Quick Reference card, cable cover

## **Ordering Information & Accessories**

PowerLite L690E V11HB25020 Replacement Air Filter (ELPAF65) V13H134AF0 Custom Micro-Adjustable Projector Mount (ELPMBPRH) V12H809001 Universal Projector Mount (ELPMBPJG) V12H808001 PowerLite Pilot™ 3 (ELPCB03) V12H927020 PixiePlus ELPSP10 PixAlign Camera (ELPEC01) V12HA46010 External Speaker (ELPSP02) V12H467020 DC-07 Document Camera V12H759020 DC-13 Document Camera V12H757020 DC-21 Document Camera V12H758020

1 4K Enhancement Technology shifts each pixel to surpass Full HD resolution on screen. | 2 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118.13 No required maintenance for the light source and filter for up to 30,000 hours (Extended Mode) or 20,000 hours (Normal Mode). Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m³ of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. I 4 The projector supports direct peer-to-peer wireless casting of local content from Miracast-enabled devices or via the Epson iProjection app. For best performance when using Epson iProjection, it is recommended that the projector and connecting devices be configured on a network, either through the Ethernet port on the projector or via a wireless connection. The Epson iProjection App does not support all files and formats. See epson.com/iprojection for details. I 5 NFC requires use of a device that includes NFC and may require additional software. I 6 Using separate camera for each projector. I 7 Requires Epson external camera for each projector and may require Epson Projector Professional Tool app. I 8 Requires an active Internet connection for alerts and Firmware download. 9 Split Screen feature requires remote control. Consult your user manual for input combinations. 10 For convenient and reasonable recycling options, visit epson.com/recycle | 11 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency. 12 Product comes with a 3-year limited warranty with the option to purchase Extended Service Plans up to a total of 5 years of continuous coverage. Extended Service Plan can be purchased at any time that you are covered under an Epson limited warranty or Epson Extended Service Plan. See individual service plan for details. I 13 Expedited shipping not available in all areas. Orders must be placed and processed by 1 p.m. Pacific Time, Monday through Friday, excluding holidays.

See the latest innovations from Epson Business Solutions at epson.com/forbusiness



Epson America, Inc. 3131 Katella Ave., Los Alamitos, CA 90720 **Epson Canada Limited** 

185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com www.epson.ca

Specifications and terms are subject to change without notice. EPSON, the 3LCD logo and PowerLite are registered trademarks and Epson iProjection is a trademark of Seiko Epson Corporation. Epson Connection, Epson Preferred Plus, Pilot and PixAlign are trademarks of Epson America, Inc. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. Miracast® and Wi-Fi® are registered trademarks of Wi-Fi Alliance®. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2025 Epson America, Inc. CPD-65464 2/25

Contact.	
	)